

ADA031905



COPY NO. 32

TECHNICAL REPORT 4991


PRELIMINARY STUDIES ON PULSED ELECTRIC
FIELD BREAKDOWN OF LEAD AZIDE

L. AVRAMI
M. BLAIS
D. DOWNS
T. GORA

OCTOBER 1976

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED.

PICATINNY ARSENAL
DOVER, NEW JERSEY



*Classified references + statement A
Accession per Mr. J. H. Norton*

*JHC
11/12/76*

The findings in this report are not to be construed
as an official Department of the Army position.

DISPOSITION

Destroy this report when no longer needed. Do not
return to the originator.

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER Technical Report 4991	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER Technical Rept.
4. TITLE (and Subtitle) Preliminary Studies on Pulsed Electric Field Breakdown of Lead Azide,		5. TYPE OF REPORT & PERIOD COVERED
6. PERFORMING ORG. REPORT NUMBER		
7. AUTHOR(s) L. Avrami, M. Blais, D. Downs, T. Gora		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS Feltman Research Laboratory Explosives Division Picatinny Arsenal, Dover, NJ 07801		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS DA1W162118AD51 AMCMS Code 61211811D5100
11. CONTROLLING OFFICE NAME AND ADDRESS		12. REPORT DATE October 1976
		13. NUMBER OF PAGES 26
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) PA-TR-4991		15. SECURITY CLASS. (of this report) Unclassified
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		16a. DECLASSIFICATION/DOWNGRADING SCHEDULE
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report) 1W162118AD51		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Lead Azide Surface Effects Electric Field Radiation Effects Initiation Contact Effects		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) Preliminary results from a study of the electric field induced breakdown of lead azide are reported. Specifically, we discuss the effects of contacts on the initiation of explosives by electric fields, and present preliminary measurements of the transient current in lead azide during the application of a pulsed voltage pulse. A circuit which eliminates the capacitive transient due to the voltage pulse is described.		

DD FORM 1 JAN 73 1473 EDITION OF 1 NOV 65 IS OBSOLETE

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

* are discussed.

282900

y/B

The citation in this report of the names of commercial firms or commercially available products or services does not constitute official endorsement or approval of such commercial firms, products, or services by the U.S. Government.

TABLE OF CONTENTS

	Page No.
Foreword	1
Introduction	2
Background	2
A. Contact Effects	2
B. Pulsed Electric Field Measurements	3
Experimental	3
A. Contact Effects	3
B. Pulsed Electric Fields	4
Discussion	6
A. Contact Effects	6
B. Transient Measurements	7
Acknowledgment	8
References	9
Distribution List	18
Figures	
1 Capacitive Sample Geometry	11
2 Schematic of the Balanced Circuit	12
3 Circuit Housing and Sample Chamber	13
4 Oscillographs of Current and Voltage vs Time	14
5 Schematic of the Triggering Circuit	15
6 Schematic of the High Voltage Test Fixtures	16
7 Equipment for the Nanosecond Pulse Experiment	17

FOREWORD

This program was sponsored by the Nuclear Weapons Effects Program Office (NWEPO), Harry Diamond Laboratory, Adelphi, Maryland under DA Project No. 1W162118AD51 on Nuclear Weapons Effects for Army Projects - Electrical Properties of Lead Azide. The technical monitor for this work was Mr. James. H. Gwaltney, NWEPO.

ACCESSION for	
WHS	Write Section <input checked="" type="checkbox"/>
WCC	Buff Section <input type="checkbox"/>
WZAN/UNGED	<input type="checkbox"/>
DATE: 11/12/76	
BY: [Signature]	
REMARKS: [Blank]	
A	

DDC
 RECEIVED
 NOV 12 1976
 REGISTRY
 D

INTRODUCTION

Lead azide has been observed to initiate when subjected to pulsed radiation during underground nuclear tests (Ref 1-3). Initiation occurred at radiation dose levels well below the thermal initiation level. It has been proposed that the initiation is caused by dielectric breakdown in an intense electric field produced in the material by the radiation pulse (Ref 2-4). Possible mechanisms for generation of this electric field are discussed elsewhere (Ref 4-8). In order to understand the initiation of lead azide by radiation-induced electric fields, it is desirable to know the behavior of the material during the application of a high voltage pulse with risetime and duration approximating that of the induced field. We describe here the development of a technique by which a well characterized voltage pulse can be applied to a pressed pellet explosive sample and the associated conduction current simultaneously monitored. In addition, we have shown that contact and surface effects dominate the dc-electric field initiation properties of lead azide; and the importance of considering this when relating pulsed field initiation results to observations from underground nuclear tests is discussed.

BACKGROUND

A. Contact Effects

Several recent investigations of the effect of electric fields on explosive azides, both in pressed pellet (Ref 9,10) and single crystal (Ref 11,12) form, have attempted to establish a threshold field for initiation or breakdown. Leopold (Ref 9) found a breakdown field of $\sim 3 \times 10^4$ volt/cm when lead azide pellets were in contact with the electrodes. However, if either one or both of the electrodes was "stood off" by a thin mylar sheet, no breakdown was observed. For example, with steady state applied voltages up to 4800 volts across a mylar/lead azide/mylar sandwich, corresponding to an average electric field of 7.4×10^4 volts/cm in the lead azide, initiation did not occur. It appears that the presence of electrical contacts on the surface of the lead azide plays an important role in electric field-assisted initiation. This conclusion is further strengthened by recent Russian work that reported experiments on pressed pellets of copper and thallium azide in which they varied the contact metals and found a dependence of the breakdown field on the metal work function (Ref 10). They attributed this to current injection presumably from ohmic contacts. Subsequently, Mark and Gora (Ref 13) performed an analysis of the Russian work, based on classical Schottky barrier theory, showing that the results are well described in terms of a barrier formed at the metal/lead azide interface whose magnitude depends on material properties, the metal work function and the applied voltage. In their model, initiation is associated with a critical field at the interface, in the region of the Schottky barrier between the metal electrode and the azide sample. Their discussion explicitly takes into account the

particulate nature of the pressed pellets.

In any case, Leopold's results on pressed pellets suggest that the presence of a conducting contact is necessary for initiation to occur at all, at least for average electric fields \bar{E} in the range of those causing initiation in the presence of contacts ($3-4 \times 10^4$ volts/cm). An average electric field \bar{E} leading to initiation in single crystal samples of lead azide, using a Au/lead azide/Au sandwich geometry, has been reported (Ref 12) to be 3.5×10^4 volts/cm. We will present below experiments performed with dc voltages which extend Leopold's pressed pellet results to higher \bar{E} values; and briefly discuss alternative interfacial mechanisms which may be responsible for initiation.

B. Pulsed Electric Field Measurements

The application of pulsed electric fields to lead azide does not exactly simulate the conditions experienced by a sample exposed to a radiation-induced electric field. It in effect separates out one of the phenomena occurring in the radiation environment, others being the increase in conductivity due to the "injection" of charge carriers by photo-compton processes and the production of charge carriers by excitation processes in the bulk.

In this work, we have developed a technique by which a well characterized voltage pulse is applied to an explosive sample and the associated conduction current simultaneously monitored. This measurement can in principle provide information about changes in conductivity occurring in response to an applied electric field in the absence of other radiation effects.

EXPERIMENTAL

A. Contact Effects

Samples were mounted between mylar insulators in the capacitive geometry shown schematically in Fig. 1. The experiment was conducted in a vacuum chamber at 2×10^{-5} torr. (The high voltage experiments reported by Leopold (Ref 9) were performed with the samples immersed in oil). Care was taken to avoid discharges from the high voltage points of the sample holder to ground. The voltage was increased in steps of 500 volts to a maximum of 5 kV, and was held constant for 60 sec. at each step. Values for \bar{E} (in the sample) were calculated from the applied voltage V_a , the thickness L appropriate to a given sample, the mylar insulator thickness $l/2$, and the dielectric constant ratio κ [dielectric constant (lead azide)/dielectric constant (mylar)], by using the relation appropriate to perfect dielectrics:

$$\bar{E} = \frac{V}{\kappa \ell + L}$$

No initiation occurred in the pressed pellet samples (pressed to $\sim 3.5 \text{ gm/cm}^3$ density, $1-3 \times 10^{-2} \text{ cm}$ thick), using the insulated electrodes, up to the highest \bar{E} -value applied, $1.4 \times 10^5 \text{ V/cm}$. This value was determined by the upper limit (5kV) of the power supply and sample geometry. Our highest \bar{E} is a factor of four greater than the \bar{E} -values that lead to initiation in contacted samples (Ref 10-12), and a factor of two greater than the highest \bar{E} -value reported by Leopold (Ref 9). The same result (no initiation) held for single crystal samples (grown by the method of Garrett (Ref 14) and cut and polished to provide parallel flat surfaces), with the highest \bar{E} -value attained being $1.02 \times 10^5 \text{ V/cm}$. The maximum \bar{E} -values were maintained on the sample for about a half-hour, and some samples were subjected to combinations of 400.0 nm irradiation (strongly absorbed by $\text{Pb}(\text{N}_3)_2$) and strong field, for both polarities, again with no effect. It has been suggested (Ref 4) that the application of such radiation may increase the local field at the irradiated surface due to changes in conductivity, and it has been observed (Ref 4) that the threshold \bar{E} -values for contacted single crystal samples decrease by a factor of two with concurrent irradiation.

B. Pulsed Electric Fields

When a voltage pulse is applied to an insulating specimen such as lead azide, it is accompanied by a substantial capacitive current pulse. This displacement current can effectively interfere with the measurement of conduction current in the material. To overcome this problem, we have designed a balanced circuit as shown in Fig. 2. On closing the mercury wetted contact relay S, the voltage $+V/2$ appears at P_2 and $-V/2$ appears at P_1 . The point P_2 is connected to the sample contact on the high voltage side and to the y-axis of one beam of a dual beam oscilloscope S_1 . P_1 is connected to a variable capacitor C_v . The internal resistance of the battery is shunted by the $12 \mu\text{f}$ capacitance in parallel so that the full voltage appears at P_1 and P_2 in approximately 10^{-7} seconds. The current through the sample is obtained by measuring the voltage developed across the load resistance R_L with the second beam of the oscilloscope connected at S_2 . Sensitivity is varied by changing R_L . C_L represents the unavoidable stray capacitance of the measuring circuit (resistors, cables, etc.). The displacement current transient due to the sample capacitance C_s is compensated by the equal and opposite transient through C_v which is adjusted to equal C_s . For a sample of thickness d , the average applied field was $V/(2d)$ where V_{max} was 2000 volts.

The entire circuit was contained in a metal box and the evacuable sample chamber was mounted on top of the box to make leads as short as possible and reduce stray capacitance. This arrangement

is shown in Fig. 3.

Samples were mounted on teflon discs, electroded with silver paint and potted in RTV. Pellets of both PVA and RD 1333 lead azide were tested. PVA lead azide samples pressed to 54,000 psi were exposed to maximum average fields of 4.9×10^4 volts/cm. Four of ten pellets tested initiated in forepump pressure vacuum ($\sim 10^{-2}$ torr). None could be initiated at ambient conditions. The time between application of the voltage and detonation was observed to vary, sometimes being greater than the duration of the oscilloscope trace. Current and voltage traces of an event which began after 22 μ s are shown in Fig. 4. Initially the current through the sample was less than 10^{-4} amp. At approximately 22 μ s, the current increased rapidly with a corresponding drop in voltage. 16 μ s later, there was a sharp drop in the voltage which is evidence for the actual detonation of the pellet.

Several pellets of RD 1333 with densities between 2.62 and 3.26 were exposed to pulsed fields as high as 6.5×10^4 volts/cm at both vacuum and ambient conditions. None of these samples could be initiated even with repeated application of the pulsed field.

As an alternative approach, designed to obtain voltage transients more similar to those produced by the radiation-induced field, a high voltage pulse generator was acquired. The Pacific Atlantic Trading Co. Model PT55 was chosen for the experiments since it is capable of producing 55 kV pulses with 2 ns risetimes and 75 ns pulse width.

A trigger pulse of at least +250V with risetime of 10 ns was required. This was accomplished with a circuit designed around a Potter-Brumfield mercury-wetted-contact relay JML-1240-81. A schematic is shown in Fig. 5.

Lead azide pellets were mounted in specially designed fixtures obtained by one of us (LA) from Sandia* and shown schematically in Fig. 6. The electrode geometry of these fixtures assures a highly uniform electric field in the region where the sample is held. In addition, the electrodes provide a reliable witness to the occurrence of a detonation. A chamber which can be evacuated or filled with various ambient gases was designed to incorporate these fixtures and can be seen in Fig. 7 along with the associated electronics.

Several lead azide pellets tested with the electrodes in direct contact and at ambient conditions were initiated with the 55 kV pulse. We have also made preliminary tests with this system using mylar standoffs between the electrodes and the pellet. With the mylar stand-offs and at atmospheric pressure, the lead azide always initiated.

* See Acknowledgment

However, in one experiment where the edge of the pellet was potted in RTV so that all air gaps between the mylar standoffs were eliminated, initiation did not occur.

DISCUSSION

A. Contact Effects

The results of our experiments on contacted and non-contacted samples in dc fields lead us to conclude that electrode interface effects dominate the field initiation of $\text{Pb}(\text{N}_3)_2$ when it is directly in contact with the electrode material. There are conflicting possibilities for the role of contacts in the mechanism leading to initiation. The electronic current injection mechanism (Ref 10) offered to account for field initiation in $\text{Cu}(\text{N}_3)_2$ and $\text{Tl}(\text{N}_3)$ explicitly requires ohmic contacts. Hot electronic carrier generation would then be unlikely because of the characteristic field distributions associated with single injection (Ref 15) so that initiation would most probably be a result of either ohmic heating, or of a high density of (reactive) excited electronic states in the form of injected carriers (Ref 16,17). For a model based on electronic carrier emission from a barrier contact (Ref 3), there are three possible mechanisms which rely on high local internal fields to generate hot electrons which lose energy by impact ionization. The first, due to O'Dwyer (Ref 18), assumes that the impact ionization causes avalanche multiplication of electronic carriers which eventually break down at the exit electrode where most of the energy is dissipated by impact - generated carriers. The second mechanism, suggested by DiStefano and Shatzkes (Ref 19), suggests that impact ionization generates a space charge in the volume of the specimen that concentrates the internal field at the emitting electrode and gates an increasing flow of emitted current with eventually catastrophic power dissipation at the entrance electrode. Finally, as there is strong evidence for ionic conductivity dominating the low - field equilibrium current (Ref 20), ionic conductivity may also be playing a role in electrode - dominated initiation. For example, electronic carriers emitted from the electrodes might attach themselves to ions (lattice ions or imperfections such as impurities and vacancies), and high - field anomalies in the ion current then might be responsible for the ultimate initiation. More experimentation is required to determine the exact nature of the interface - dominated initiation process.

These results are particularly important in the analysis of experiments designed to simulate the response of lead azide to a radiation-induced electric field. It has been proposed that the induced field arises in the sample bulk due to the separation of charge produced by the radiation (Ref 2,3,7), a situation presumably different than that of a high field at the sample-electrode interface. In the electroded experiments the contact provides the charge carriers which are emitted into the bulk through the high field region

formed at the interface. One would expect quite different field distributions in the bulk during radiation experiments as a consequence of the photo-carriers generated by the radiation. Therefore, care must be exercised in correlating results from the two types of experiments.

B. Transient Measurements

The circuit designed to compensate for the displacement current arising from the polarization of the sample is quite suitable for the purpose of measuring current through the sample. We suspect, however, that no current is injected from the contacts and that currents originate only by emission from the Schottky barrier when sufficiently high voltages are attained. The current then increases rapidly by one of the avalanching processes discussed above. This is supported by the data shown in Fig. 4. After application of the voltage the measurable current is less than 10^{-4} amp. It is interesting to note that the pellet does not initiate as the voltage is applied but there is a measurable delay time. Also, the actual detonation, indicated by the sharp drop in voltage, follows a short period during which a relatively high current flows through the pellet.

Although the above result demonstrated that the experimental technique is quite applicable to the study of electric field initiation of explosives, it became clear that pulses of shorter duration would have to be higher in magnitude in order to achieve initiation. The original circuit was limited to rise times of $\sim 10^{-7}$ sec and maximum voltage of 2000 volts.

Our preliminary experiments with the shorter rise time high voltage transient generator indicate that with metal contacts lead azide pellets are readily initiated. The next step in the program should be to incorporate the high voltage generator into a balanced circuit similar to the one described above with appropriate instrumentation to record voltage and current response in nanosecond time frames. In addition, the experiments should be performed with both electroded and non-electroded sample geometries. It appears that very high fields can be applied, at least for short times, without initiation if the sample is not contacted. The effect of simultaneous irradiation under this condition would be interesting.

ACKNOWLEDGMENT

The authors are very grateful to Mr. C.G. Scott and Dr. J.E. Gover, Sandia Laboratories, Albuquerque, New Mexico for making available the specially designed fixtures in which lead azide pellets were mounted in a highly uniform electric field.

REFERENCES

1. Gover, J.E., "Results of Underground Tests on Explosive Components (U)", Proceedings of the Second Annual Meeting of the Nuclear Survivability Working Group on Propulsion and Ordnance Systems, Aerospace Corporation Report No. TOR-0172 (S2320-01)-6, Vol. 1, 15 September 1971 (SRD).
2. Brown, N.E., Gover, J.E., Hartman, E.F., Morgan, D.L., and Scott, C.G., "Radiation Initiation of Lead Azide (U)", Proceedings of Third Annual Meeting of Nuclear Survivability Working Group on Propulsion and Ordnance, Defense Nuclear Agency Report, DNA 2987P, Vol. 1, 10 October 1973 (ARD).
3. Hartman, E.F., Scott, C.G., Gover, J.E., and Brumley, F.B., "The Initiation Mechanism of Lead Azide at Low Dose Levels in a Radiation Environment (U)", Sandia Laboratories Report SLA-74-0168, August 1974 (SRD).
4. Scott, C.G., Gover, J.E., Hartman, E.F., Morgan, D.L., Brown, N.E., and Schwiner, J.E., "IEMP Effects in Lead Azide (U)", Proceedings of the IEMP Symposium Defense Nuclear Agency Report DNA-3098P, February 1973 (SRD).
5. Zimmerschied, A. and Davies, F.W., "Investigations of Lead Azide Dielectric Strength", Boeing Company Document T2-4096-1, July 1974.
6. Davies, F.W. and Shrader, J.W., "The Radiation Induced Conductivity of Lead Azide", Proceedings of Fifth Symposium on Nuclear Survivability of Propulsion and Ordnance Systems, Stanford Research Institute, Menlo Park, California, 7-9 October 1975 (in publication).
7. Hays, S.D. and Seay, G.E., "Radiation - Induced Electric Field Initiation of Lead Azide", Proceedings of Fifth Symposium on Nuclear Survivability of Propulsion and Ordnance Systems, Stanford Research Institute, Menlo Park, California, 7-9 October 1975 (in publication).
8. Borgardt, F.G., Quinn, J.R., and Avrami, L., "Nuclear Vulnerability of Selected Ordnance Items (U)", Technical Report 4853, Picatinny Arsenal, Dover, NJ, April 1975 (ARD).
9. Leopold, H.S., "Exposure of Primary Explosives to Applied Electric Fields", Naval Ordnance Laboratory Technical Report 73-125, August 1973.
10. Zakharov, Y.A. and Sukhushin, Y.N., Izv. Tomsk. Politekh. Inst. 251, 213 (1970).

11. Downs, D.S. et al., Technical Report 4711, Picatinny Arsenal, Dover, NJ, September 1974.
12. Downs, D.S. et al., Technical Report 4874, Picatinny Arsenal, Dover, NJ, November 1975.
13. Mark, P. and Gora, T., J. Sol. State Chem. 15, 79 (1975).
14. Garrett, W.L., Mat. Res. Bull. 7, 949 (1972).
15. Lampert, M.A. and Mark, P., Current Injection in Solids, Academic Press, New York, 1970.
16. Williams, F.E. in Chemical Dynamics, Hirshfelder, J.O. and Henderson, D., Eds., Wiley Interscience, New York, 1971, p. 289.
17. Fair, Jr., H.D., Downs, D.S., Forsyth, A.C., Garrett, W., Blais, M., Gora, Jr., T.F., and Williams, F.E., Technical Report 4607, Picatinny Arsenal, Dover, NJ, December 1973.
18. O'Dwyer, J.J., J. Appl. Phys., 40, 3887 (1969).
19. DiStefano, T.H. and Shatzkes, M., Appl. Phys. Lett., 25, 685 (1974); J. Vac. Sci. Tech. 12, 493 (1975).
20. Savel'ev, G.G., Zakharov, Yu. A., and Shechkov, G.T., Russ. J. Phys. Chem., 41, 904 (1967).




Fig 1 Capacitive Sample Geometry





Fig 2 Schematic of the Balanced Circuit



(a)



(b)

Fig 3 Circuit Housing and Sample Chamber




Fig 4 Oscillographs of Current and Voltage vs Time




Fig 5 Schematic of the Triggering Circuit




Fig 6 Schematic of the High Voltage Test Fixtures




Fig 7 Equipment for the Nanosecond Pulse Experiment

DISTRIBUTION LIST

Copy No.

Commander Picatinny Arsenal ATTN: SARPA-TS-S Dover, NJ 07801	1-5
Commander US Army Armament Research and Development Command ATTN: Dr. R. Weigle Picatinny Arsenal Dover, NJ 07801	6
Commander US Army Materiel Development and Readiness Command ATTN: DRCDE	7
DRCDMA-ST, Mr. N. Klein	8
DRCDE-DM, Mr. L. Flynn	9
5001 Eisenhower Avenue Alexandria, VA 22333	
Commander US Army Armament Command ATTN: AMSAR-RD-T	10
AMSAR-SF	11
AMSAR-RD, Dr. J.A. Brinkman	12
AMSAR-ASF	13
Rock Island, IL 61201	
Commander US Army Ballistic Research Laboratories ATTN: Technical Library	14
Dr. R.J. Eichelberger, Director	15
Dr. I. May	16
Dr. E. Freeman	17
DRXBR-XA, Mr. J. Meszaros	18
Aberdeen Proving Ground, MD 21005	
Commander Army Research Office ATTN: Dr. D.R. Squires	19
Dr. R. Ghirardelli	20
Dr. M. Ciftan	21
Dr. I. Lefkowitz	22
P.O. Box 12211 Research Triangle Park, NC 27709	

Commander US Army Harry Diamond Laboratories ATTN: DRXDO-NP, Mr. J. Gwaltney Technical Library 2800 Powder Mill Road Adelphi, MD 20783	23-27 28
Headquarters Department of the Army ATTN: DAMA-CSM-N/LTC G. Ogden Washington, DC 20310	29
Director Defense Nuclear Agency ATTN: DDST/Dr. M.C. Atkins Dr. D.C. Oakley Washington, DC 20305	30 31
Commander US Army Nuclear Agency ATTN: ATCN-W/COL A. Deverill Ft. Bliss, TX 79916	32
Commander US Army Missile Command ATTN: AMSMI-RRR/Dr. F. Gibson DRCPM-PE/Mr. W. Jann Redstone Arsenal, AL 35809	33 34
Director Ballistic Missile Defense Advanced Technology Center ATTN: Mr. Melvin Capps P.O. Box 1500 Huntsville, AL 35807	35
Commander Ballistic Missile Defense Systems Command ATTN: BMDSC-TEN/Mr. J. Veeneman P.O. Box 1500 Huntsville, AL 35807	36
Defense Documentation Center Cameron Station Alexandria, VA 22314	37-38
Commander Air Force Rocket Propulsion Laboratory ATTN: DYSS/Mr. G.A. Beale Edwards AFB, CA 93523	39

Navy Department Strategic Systems Project Office ATTN: Mr. F.S. Vandersmith Washington, DC 20376	40
Naval Research Laboratory ATTN: Mr. G. Cooperstein Washington, DC 20360	41
Commander Space and Missile Systems Organization ATTN: MNNH/MAJ M. Baran Norton AFB, CA 92409	42
Sandia Laboratories ATTN: Dr. J.E. Gover Dr. D.B. Hayes, Div 2513 Dr. D.E. Munson, Div 5163 Dr. N. Brown Technical Library P.O. Box 5800 Albuquerque, NM 87115	43 44 45 46 47
Brookhaven National Laboratory ATTN: Dr. P.W. Levy/Physics Dept Upton, NY 11973	48
Commander US Naval Weapons Center (Code 753) ATTN: Technical Library China Lake, CA 93555	49
Commander US Naval Surface Weapons Center ATTN: Technical Library Mr. I. Kabik Dr. P.J. DiBona White Oak, Silver Spring, MD 20910	50 51 52
US Naval Ordnance Station ATTN: Library Indian Head, MD 20640	53
Commander Frankford Arsenal Pittman-Dunn Laboratories ATTN: Dr. J. Lannon Bridge and Tacony Streets Philadelphia, PA 19137	54

Explosives Research Laboratories Bureau of Mines ATTN: Dr. R.W. Watson Pittsburgh, PA 15230	55
Headquarters Air Force Weapons Laboratory (WLX) Kirtland Air Force Base, NM 87117	56
Commander Armament Development and Test Center Eglin AFB ATTN: Dr. L. Elkins Valpariso, FL 32542	57
Los Alamos Scientific Laboratory ATTN: WX-2, Dr. L. Smith WX-3, Dr. A. Popolato WX-7, Dr. G. Seay Technical Library Los Alamos, NM 87544	58 59 60 61
Lawrence Livermore Laboratory ATTN: Technical Library Mr. B. Dobratz Dr. F. Walker P.O. Box 808 Livermore, CA 94550	62 63 64
Air Force Office of Scientific Research 1400 Wilson Boulevard Arlington, VA 22209	65
Stanford Research Institute Fluid Physics and Detonation Dynamics Dept. ATTN: Dr. M. Cowperthwaite Menlo Park, CA 34025	66
US Atomic Energy Commission ATTN: Division of Technical Information Oak Ridge, TN 37830	67
Mr. Jack R. Polson Mason and Hanger - Silas Mason Co. Development Section, IAAP Burlington, IA 52601	68

Martin-Marietta Laboratory ATTN: Dr. N. Maycock South Rolling Road Baltimore, Maryland	69
Dr. J.F. Riley (52-11,204) Lockheed Palo Alto Research Laboratory 3251 Hanover Street Palo Alto, CA 94304	70
Dr. Peter Mark Department of Electrical Engineering Princeton University Princeton, NJ 08540	71
Dr. F.E. Williams Department of Physics University of Delaware Newark, DE 19711	72
Mr. R. Thompson Franklin Institute Research Laboratory Benjamin Franklin Parkway Philadelphia, PA 19103	73
The Boeing Company ATTN: Mr. Frank Davies (Mail Stop 42-37) P.O. Box 3999 Seattle, Washington 98124	74
Commander Picatinny Arsenal ATTN: SARPA-ND-W, Mr. D. Waxler SARPA-FR-E-S, Mr. L. Avrami Dover, NJ 07801	75 76-91